P.O Box 94 Mt. Calvary, WI 53057 920-753-4691

S

# New Home Construction Permit Application One and Two Family Residential Homes

Location						Permit #		
Owner						Date		
Address			City		State		Zip	
Phone				Email				
Parcel #					Zoning			
Contractor								
Address			City		State		Zip	
Phone				Email				
License #				Contact Person:				
					Project	t Descriptior	1:	
Housing Type	Single Family	Two Family		Square Footage		Cost \$		
Fee Schedule				Make Check Payable to:				
0 to 2000 Sq	-		\$350.00					
2001-5000 S	-		\$400.00 \$500.00		Town of Marshfield			
5000 Sq. Ft F Electrical Se		Ι	\$500.00	\$50.00	Retur	Return Application and Check to:		
Electrical Pe				\$100.00				
Plumbing Pe	ermit			\$150.00	Witkow	ion Agency, LLC		
HVAC Permi				\$100.00	62	P.O. Box 98		
State Permit Seal				\$40.00	ļ	Kiel, WI 53042		
	Ad	ditional Fee Schedule		to				
Escrow	) e e = 4	Returnable upon occupancy	<b>#0 =</b> 0.0	\$300.00		For Income 1	ona Calli	
Driveway/ R Fire Number			\$25.00 \$75.00		1	For Inspecti	UIIS Call:	
Fire Number Sign \$75.00 Land Use Permit - Project Cost x \$.001			\$75.00		Witkov	vski Incnact	ion Agency, LLC	
			Total		1	Brian Witl Office: 920-2	kowski	
	Additional Permits May Be Required					Cell: 920-9		
		ects located on Wolf Lake; Dar	1- 920-929-3139		<u> </u>			
Sanitary Per	mit - Fond o	du Lac County			J			

	Electrical-	Plumbing- HV	AC Permit Ap	oplications		
Electrical Permit:	Company				Phone #	
	New Service	ОН	UG			
	Service Change	ОН	UG	OH to UG		
	All Services	Volts/ Amps				
		Number of Met	ers			
		Service Utility				
		Phase				
	Remodel	Location of Ser	vice			
	Outbuilding					
	Alternative Energy Installa	tion				
Signature of			Master Electric	ian License #		
Licensed Electrician		Contractor's License #				
Plumbing Permit:	Company				Phone #	
r tumbing r er mit.	Floor Drains		Sump Pump		-	Sinks
	Dishwasher		Hose Bibs			Lav's
	Showers		Water Softener	•		Bath Tub
	Garbage Disposal		Other			Water Closets
	Bar Connection		Other			Laundry Box
and with the conditions of the on the Department or Munic	e applicant agrees to comply with t his permit, understands that the iss cipality, certifies that all the inform n of Plumbing as herein described.	uance of the permit c	reates no legal liabili	ity, expressed or i	mplied	
HVAC Permit	Company				Phone #	
	New Furnace			-	Wood Burner	
	New Boiler			Replacemen	t of Equipment	
	Unit Heater(s)	_		Air Condition	-	
	Roof Top Unit(s)	_		Ventilation		
	Addition to existing system	1		Other		
Description of Work						
Type of Fue						
	BTU Heat Loss					
	t (BTU Rating)	annost and applies for	a normit to do the u	Output	had and	Input
hereby agrees that such wor	nat all of the above information is co rk will be done in accordance with compliance with the Wisconsin Hear	the descriptions set fo	orth herein; and it is	further agreed th		
Signature of					<b>.</b> .	
HVAC Contractor					License #	

		Page 2				
Erosion Contro	ol Application					
Owner's Name						
Address of Project						
City/ Village	State	Zip				
Phone #	Email					
Contractor's Name						
Address						
City/ Village	State	Zip				
Phone #	Email					
Type of Erosion Control to be Installed	Separate Site Plan Included	Yes				
	- F	No				
Silt Fence Bales	VegetationErosion Mat					
I, the undersigned Owner/ Contractor, do hereby agree to comply with SPS 321.125 & 321.126 of the Wisconsin Department of Safety & Professional Services building code viewable at dsps.wi.gov/sb/SB-DIVCodesListing.html						
Signature of Homeowner	Date					
or						

Signature of Contractor

Date

### **New Home Construction Required Checklist Items**

## **County Required Items if in Shoreland Zoning**

Completed County Land Use Permit

Site Plan from County with all houses & garage dimensions

Address from County if not in a sub-division

### **Town Required Items**

Copy of Sanitary Permit
Completed Wisconsin Uniform Building Permit- Online www.eSLA.wi.gov
2 Sets of Building Plans showing all house dimensions
Completed Energy Worksheet
Completed Erosion Control Application
Completed Site Plan showing all Erosion Control
Culvert Permit if Applicable
Read and Sign the Town of Marshfield Permit Attachment
Read and Sign the Conditions of Approval Sheet
Site Plan for Town with all houses and garage dimensions

Type of Driveway being applied for:  20' to 20' to 20' New Residential Driveway   Location of Driveway you are applying for:   1. Name of the nearest intersection of Town, County, or State Roads:   2. Driveway location is approximately		Drivew	vay/ Cul	vert Permit App	lication- Town Road	1		
	Type of	Driveway being applied for:						
		20' to	30' New Re	esidential Driveway				
1. Name of the nearest intersection of Town, County, or State Roads::         2. Driveway location is approximately		Reloca	ation of an	Existing Driveway				
2. Driveway location is approximately (Miles) (N, E, S, W) of said intersection	Location	n of Driveway you are applying f	or:					
<ul> <li>3. Looking both ways down the road, is vision clear for 600'( Feet) Yes No</li> <li>4. This driveway will result in how many driveways serving this property?</li> <li>** Applicant shall place stakes in ditch line where he/she wants to place the driveway so the proposed location will be inspected and has been approved by the Town or Designees.</li> <li>** Applicant shall place stakes in ditch line where he/she wants to place the driveway so the proposed location aright of way shall be restored by and at the expense of the applicant, to the condition existent prior to such disturbance and to the satification of the Town Board or its designated appointee.</li> <li>8. The entire cost of the driveway construction or installation shall be the obligation of the applicant.</li> <li>C. Applicant shall keep driveway on or over Town Road right-of-way shall be the responsibility of the applicant.</li> <li>Applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge.</li> <li>B. The centerline of the driveway on or over Town Road right-of-way shall be the responsibility of the applicant.</li> <li>C. Driveway width is measured at the ditch line and is equal to the actual drivable width.</li> <li>B. Culver traderials are restricted to Corrugated Steel, Concrete, and/or Corrugated Polythylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular covere.</li> <li>C. All new driveways are to be constructed or this permit.</li> <li>All new driveways are to be constructed or this permit.</li> <li>All new driveways are to be constructed to the baye permanently vegetated sloped sides, unlear line.</li> <li>All new driveways are to be constructed to have permanently vegetated sloped sides, unlear line.</li> <li>All new driveways hall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be sed or sodded by the owner.<!--</td--><td>1. Name</td><td>of the nearest intersection of Tow</td><td>n, County,</td><td>or State Roads:</td><td></td><td></td><td></td></li></ul>	1. Name	of the nearest intersection of Tow	n, County,	or State Roads:				
<ul> <li>3. Looking both ways down the road, is vision clear for 600'( Feet) Yes No</li> <li>4. This driveway will result in how many driveways serving this property?</li> <li>** Applicant shall place stakes in ditch line where he/she wants to place the driveway so the proposed location will be inspected and has been approved by the Town or Designees.</li> <li>** Applicant shall place stakes in ditch line where he/she wants to place the driveway so the proposed location aright of way shall be restored by and at the expense of the applicant, to the condition existent prior to such disturbance and to the satification of the Town Board or its designated appointee.</li> <li>8. The entire cost of the driveway construction or installation shall be the obligation of the applicant.</li> <li>C. Applicant shall keep driveway on or over Town Road right-of-way shall be the responsibility of the applicant.</li> <li>Applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge.</li> <li>B. The centerline of the driveway on or over Town Road right-of-way shall be the responsibility of the applicant.</li> <li>C. Driveway width is measured at the ditch line and is equal to the actual drivable width.</li> <li>B. Culver traderials are restricted to Corrugated Steel, Concrete, and/or Corrugated Polythylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular covere.</li> <li>C. All new driveways are to be constructed or this permit.</li> <li>All new driveways are to be constructed or this permit.</li> <li>All new driveways are to be constructed to the baye permanently vegetated sloped sides, unlear line.</li> <li>All new driveways are to be constructed to have permanently vegetated sloped sides, unlear line.</li> <li>All new driveways hall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be sed or sodded by the owner.<!--</td--><td>2. Drives</td><td>way location is approximately</td><td></td><td>(Miles)</td><td>( N, E, S, W) of</td><td>said intersection</td><td></td></li></ul>	2. Drives	way location is approximately		(Miles)	( N, E, S, W) of	said intersection		
** Applicant shall place stakes in dich line where he/she wants to place the driveways on the proposed location will be inspected and has been approved by the Town or Designees.  Pumer's Covenant  A. Any grading, special ditching, alteration of slope or any other disturbance of any portion of the road right-of-way shall be restored by and at the expense of the applicant, to the condition existent prior to such disturbance and to the satification of the Town Board or tis designated appointee. B. The entire cost of the driveway construction or installation shall be the obligation of the applicant. C. Applicant shall keep driveway/ culvert free of debris and obstructions to provide proper drainage along the road D. Maintenance and upkeep of driveway on or over Town Road right-of-way shall be the responsibility of the applicant B. Applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge. F. The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary. C. Driveway width is measured at a los equal to the actual drivable width. H. Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover I. The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly apointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit. J. All new driveways shall be seed or sodded by the owne. K. Construction needs a negative grade as to not drain onto the road regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application septication. Signature			ion clear fo				No	
** Applicant shall place stakes in dich line where he/she wants to place the driveways on the proposed location will be inspected and has been approved by the Town or Designees.  Pumer's Covenant  A. Any grading, special ditching, alteration of slope or any other disturbance of any portion of the road right-of-way shall be restored by and at the expense of the applicant, to the condition existent prior to such disturbance and to the satification of the Town Board or tis designated appointee. B. The entire cost of the driveway construction or installation shall be the obligation of the applicant. C. Applicant shall keep driveway/ culvert free of debris and obstructions to provide proper drainage along the road D. Maintenance and upkeep of driveway on or over Town Road right-of-way shall be the responsibility of the applicant B. Applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge. F. The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary. C. Driveway width is measured at a los equal to the actual drivable width. H. Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover I. The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly apointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit. J. All new driveways shall be seed or sodded by the owne. K. Construction needs a negative grade as to not drain onto the road regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application septication. Signature	4. This d	lriveway will result in how many d	rivewavs s	erving this property?				
will be inspected and has been approved by the Town or Designees.         Description of the inspective of the applicant, to the condition existent prior to such disturbance and to the satification of the Town Board or tis designated appointee.         B.       The entire cost of the driveway construction or installation shall be the obligation of the applicant.         C.       Applicant shall keep driveway (ulver free of debris and obstructions to provide proper drainage along the road on the asplicant to the applicant to the applicant.         B.       Maintenance and upkeep of driveway on or over Town Road right-of-way shall be the responsibility of the applicant the pavement edge.         B.       The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement edge.         F.       The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary.         G.       Driveway widh is measured at the ditch line and is equal to the actual drivable width.         H.       Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover         1.       The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duy appointed agents and employees against any action for personal linury or property damage sustained by reason of the issuance or exercise of this permit.         J.       All new drive			-		ce the driveway so the pr	oposed location		
A. Any grading, special ditching, alteration of slope or any other disturbance of any portion of the road right-of-way shall be restored by and at the expense of the applicant, to the condition existent prior to such disturbance and to the satification of the Town Board or its designated appointee.         B. The entire cost of the driveway construction or installation shall be the obligation of the applicant.         C. Applicant shall keep driveway (culvert free of debris and obstructions to provide proper drainage along the road         D. Maintenance and upkeep of driveway on or over Town Road right-of-way shall be the responsibility of the applicant.         E. Applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge.         F. The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary.         G. Driveway width is measured at the ditch line and is equal to the actual drivable width.         H. Culvert materials are restricted to: Corrugated Steel, Correte, and/Or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover         I. The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustaned by reason of the issunce or exercise of this permit.         J. All new driveways are to be construction shall be accomplished using only soil materials. The isde slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes		-						
A. Any grading, special ditching, alteration of slope or any other disturbance of any portion of the road right-of-way shall be restored by and at the expense of the applicant, to the condition existent prior to such disturbance and to the satification of the Town Board or its designated appointee.         B. The entire cost of the driveway construction or installation shall be the obligation of the applicant.         C. Applicant shall keep driveway (culvert free of debris and obstructions to provide proper drainage along the road         D. Maintenance and upkeep of driveway on or over Town Road right-of-way shall be the responsibility of the applicant.         E. Applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge.         F. The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary.         G. Driveway width is measured at the ditch line and is equal to the actual drivable width.         H. Culvert materials are restricted to: Corrugated Steel, Correte, and/Or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover         I. The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustaned by reason of the issunce or exercise of this permit.         J. All new driveways are to be construction shall be accomplished using only soil materials. The isde slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes				<b>Owner's Cove</b>	nant			
such disturbance and to the satification of the Town Board or its designated appointee. B. The entire cost of the driveway construction or installation shall be the obligation of the applicant. C. Applicant shall keep driveway (culvert free of debris and obstructions to provide proper drainage along the road D. Maintenance and upkeep of driveway on or over Town Road right-of-way shall be the responsibility of the applicant E. Applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge. F. The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary. G. Driveway width is measured at the ditch line and is equal to the actual drivable width. H. Culvert materials are restricted to: Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover I. The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit. J. All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway and at the owner. K. Construction needs a negative grade as to not drain onto the road I. hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application. Signature	А.							
B.       The entire cost of the driveway construction or installation shall be the obligation of the applicant.         C.       Applicant shall keep driveway/ culvert free of debris and obstructions to provide proper drainage along the road         D.       Maintenance and upkeep of driveway on or over Town Road right-of-way shall be the responsibility of the applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge.         F.       The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary.         G.       Driveway width is measured at the ditch line and is equal to the actual drivable width.         H.       Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12° inches of granular cover         I.       The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit.         J.       All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway hall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner.         K.       Construction needs a negative grade as to not drain onto the roa								
C. Applicant shall keep driveway/ culvert free of debris and obstructions to provide proper drainage along the road D. Maintenance and upkeep of driveway on or over Town Road right-of-way shall be the responsibility of the applicant E. Applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge. F. The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary. G. Driveway with is measured at the ditch line and is equal to the actual drivable width. H. Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover I. The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit. J. All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner. K. Construction needs a negative grade as to not drain onto the road I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application. Signature	R					nlicant		
along the road D. Maintenance and upkeep of driveway on or over Town Road right-of-way shall be the responsibility of the applicant E. Applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge. F. The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary. G. Driveway width is measured at the ditch line and is equal to the actual drivable width. H. Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover I. The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit. J. All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner. K. Construction needs a negative grade as to not drain onto the road I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application. Signature								
of the applicant       E.       Applicant may not develop any driveway with-in the setbacks set by the Town. The setback shall be measured parallel to the pavement edge.         F.       The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary.         G.       Driveway width is measured at the ditch line and is equal to the actual drivable width.         H.       Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover         I.       The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit.         J.       All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner.         K.       Construction needs a negative grade as to not drain onto the road         I. hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application.         Signature       Date         Note					r r r r r			
be measured parallel to the pavement edge. F. The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary. G. Driveway width is measured at the ditch line and is equal to the actual drivable width. H. Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover I. The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit. J. All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner. K. Construction needs a negative grade as to not drain onto the road I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations. Signature Date	D.		veway on c	or over Town Road rig	ht-of-way shall be the resp	onsibility		
F.       The centerline of the driveway lying on the county right-of-way shall be at approximately right angles to the pavement except as topography may make angular placement necessary.         G.       Driveway width is measured at the ditch line and is equal to the actual drivable width.         H.       Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover         I.       The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit.         J.       All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner.         K.       Construction needs a negative grade as to not drain onto the road         I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application.         Signature	E.		-		et by the Town. The setbac	k shall		
angles to the pavement except as topography may make angular placement necessary. G. Driveway width is measured at the ditch line and is equal to the actual drivable width. H. Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover I. The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit. J. All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner. K. Construction needs a negative grade as to not drain onto the road I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application. Signature Date	F	· · ·	0		chall he at approximately	right		
G.       Driveway width is measured at the ditch line and is equal to the actual drivable width.         H.       Culvert materials are restricted to: Corrugated Steel, Concrete, and/or Corrugated Polyethylene pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover         I.       The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit.         J.       All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner.         K.       Construction needs a negative grade as to not drain onto the road         I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application.         Signature	г.	-				igni		
pipe meeting AASHTO M 294, Type 5 Specifications, with a minimum of 12" inches of granular cover  I. The permittee, his/her successors or assigns, agree to hold harmless the Town of Marshfield and its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit. J. All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner. K. Construction needs a negative grade as to not drain onto the road I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application. Signature Date	G.							
its duly appointed agents and employees against any action for personal injury or property damage sustained by reason of the issuance or exercise of this permit. J. All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner. K. Construction needs a negative grade as to not drain onto the road I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application. Signature Date Date Culvert required under driveway YES NO Diameter Length Length Date	H.	pipe meeting AASHTO M 294, T						
sustained by reason of the issuance or exercise of this permit. J. All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner. K. Construction needs a negative grade as to not drain onto the road I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application. Signature Date Date	I.	- ,	-	-				
J.       All new driveways are to be constructed to have permanently vegetated sloped sides, unless the road/ street has curb and gutter. Such construction shall be accomplished using only soil materials. The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner.         K.       Construction needs a negative grade as to not drain onto the road         I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application.         Signature       Date         Note*       Diameter of culvert to be determined by Town Board         Culvert required under driveway       YES       NO       Diameter       Length         Conditions		its duly appointed agents and employees against any action for personal injury or property damage						
The side slopes of the driveway shall be sloped at no more than a length to height ratio of 2.5:1 All slopes shall be seed or sodded by the owner. K. Construction needs a negative grade as to not drain onto the road I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application. Signature Date Note* Diameter of culvert to be determined by Town Board Culvert required under driveway YES NO Diameter Length Permit Approved by Date	J.	All new driveways are to be con	nstructed to	o have permanently v				
All slopes shall be seed or sodded by the owner. K. Construction needs a negative grade as to not drain onto the road I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application. Signature Date Note* Diameter of culvert to be determined by Town Board For Town Use Only Culvert required under driveway YES NO Diameter Length Conditions Date								
K. Construction needs a negative grade as to not drain onto the road          I, hereby certify that I have read the Owner's Covenant and understand and agree to abide by the following special regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application.         Signature					a length to height ratio of	2.5:1		
regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application.  Signature Date Date Date Conditions For Town Use Only Length Length Length Permit Approved by Date	К.	-	-		ad			
regulations and provisions of this permit and all applicable provisions and restrictions which are shown on this application.  Signature Date Date Date Conditions For Town Use Only Length Length Length Permit Approved by Date		I, hereby certify that I have read	l the Owne	r's Covenant and unde	erstand and agree to abide	by the following special	1	
Signature     Date       Note*     Diameter of culvert to be determined by Town Board       For Town Use Only       Culvert required under driveway     YES       NO     Diameter       Conditions       Permit Approved by     Date		regulations and provisions of t			0			
Note*       Diameter of culvert to be determined by Town Board         For Town Use Only         Culvert required under driveway       YES       NO       Diameter       Length         Conditions       Date	app	lication.						
For Town Use Only         Culvert required under driveway       YES       NO       Diameter       Length         Conditions	Signatu	re				Date		
For Town Use Only         Culvert required under driveway       YES       NO       Diameter       Length         Conditions	Note*	Diameter of culvert to be deter	nined by T	own Board				
Conditions				For Town Use O				
Permit Approved by Date		• •				Length		
						ate		
		<u>rr</u>					Page 5	

### **Mailbox Size & Construction Standards**

A mailbox with the Postmaster General's (PMG) seal of approval meets USPS size and construction standards.

If you build your own or buy a custom-made one, it must meet the PMG Standards. Show your local postmaster your mailbox plans or your custom-made box for approval.

### Where to Place the Mailbox (Roadside/ Curbside)

Here are some helpful guidelines to follow when placing your mailbox:

- Position your mailbox 45" to 47" from the road surface to the bottom of the mailbox or point of entry.
- Place your mailbox 8" to10" back from the curb/ road edge.
- Put your house number on the mailbox.
- If your mailbox is on a different street from your house, put your full address on the mailbox.

#### **Installing the Mailbox Post**

The Federal Highway Administration recommends:

- A 4 x 4 wooden support or a 2" diameter standard steel or aluminum post
- Avoid unyielding and potentially dangerous supports like heavy metal pipes, concrete posts, and farm equipment (e.g.- milk cans filled with concrete)
- Bury your post no more than 24"

#### Maintenance

Mailboxes take a beating from the weather, so we recommend an annual mailbox checkup to avoid damage to your mail or difficultly identifying your address.

- Tighten loosen hinges on the door
- Take care of rusty or loosen parts
- Replace missing or fading house numbers
- Keep the path to your mailbox clear

#### NOTE\* PLEASE SEE YOUR LOCAL POSTMASTER FOR RULES AND REGULATIONS FOR INSTALLATION OF MAILBOX

This picture represents the correct size for the mailbox.

